

Table E417.17-1

Radio frequency receiving system Acceptance	Section E417.13	Quantity Tested		
		Cable	Coupler	Antenna
Component Examination:	E417.5			
Visual Examination	E417.5(b)	100%	100%	100%
Dimension Measurement	E417.5(c)	100%	100%	100%
Identification Check	E417.5(e)	100%	100%	100%
Performance Verification:	E417.3(d)			
Status-of-Health ⁽¹⁾	E417.17(b)	-	-	100%
Link Performance ⁽¹⁾	E417.17(c)	100%	100%	-
Isolation ⁽¹⁾	E417.17(d)	-	100%	-
Abbreviated Antenna Pattern	E417.17(g)	-	-	100%
Abbreviated Performance Verification:	E417.3(e)			
Abbreviated Status-of-health ⁽²⁾	E417.17(e)	100%	100%	100%
Operating Environment Tests:	E417.13			
Thermal Cycling	E417.13(d)	100%	100%	100%
Acoustic	E417.13(c)	-	100%	100%
Random Vibration	E417.13(b)	-	100%	100%
Tensile Load	E417.13(f)	100%	-	-
Abbreviated Antenna Pattern	E417.17(g)	-	-	100%

⁽¹⁾ A component must undergo this test before the first and after the last operating environment test.

⁽²⁾ A component must undergo this test during each operating environment test.